



Saab Oil Guide

Saab
Original



Orio offers smart part solutions and is the exclusive supplier of Saab Original Parts.

Saab Oil Guide

Changing your oil is an essential part of ongoing vehicle maintenance to keep your car running safely.

For those who don't spend a lot of time under the hood, car maintenance can be intimidating, but it doesn't have to be. Whether you're a motor oil expert or not, we all know that oil changes are necessary.

But why?

As you drive your car, your motor oil and oil filter become contaminated. At this point, they can no longer do their jobs of protecting your engine and must be changed.

We created a guide to help you determine the right motor oil and oil filter for your Saab to keep it running at peak performance.

When does my Saab need an engine oil change?

Every 5000 miles or once a year, whichever comes first.

What kind of oil do I use and how much does it take for my model?

Use the chart below to find the recommended oil (highlighted in BLUE) and quantity for your model. Click on the hyperlink to see your oil.

What oil filter do I use and do I need anything else?

Use the chart below to find your parts for your model. Click on the hyperlink to buy.



Model	Year	Engine	Recommended Oil Type	Recommended Viscosity	Oil Quantity	Oil Filter Part Number	Associated Parts	Service Interval
C900	1979-1993 incl 1994 Convertible	B201, B202, B212	Conventional, Semi or Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30, 10W-40, 5W-30, 5W-40, 15W- 40 may be used except in cold weather	4.5Qts	93186554 4-Cyl	9132929 Drain Plug	Every 5000 miles or once a year, whichever comes first
							9132937 Gasket-Oil Drain plug	
9000	1986-1989	B202	Conventional, Semi or Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30, 10W-40, 5W-30, 5W-40, 15W- 40 may be used except in cold weather	4.5Qts	93186554 4-Cyl	7563042 Drain Plug	Every 5000 miles or once a year, whichever comes first
							7522709 Gasket	
9000CS	1990-1998	B234, B308i	Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30, 10W-40, 5W-30, 5W-40, 15W-40 may be used except in cold weather. For areas with temp above 60°F 15W-50 or 20W-50 may be used.	4Cyl 4.2Qts	93186554 4-Cyl	7563042 Drain Plug	Every 5000 miles or once a year, whichever comes first
							7522709 Gasket-Oil Drain plug	
					6Cyl 4.7Qts	6Cyl 93178952	90409376 Drain Plug	
							11016282 Gasket-Oil Drain plug	
NG 900	1994-1998	B204, B234, B258	Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30, 10W-40, 5W-30, 5W-40, 15W- 40 may be used except in cold weather. For areas with temp above 60°F 15W-50 or 20W- 50 may be used.	4Cyl 4.2Qts	93186554 4-Cyl	9132929 Drain Plug	Every 5000 miles or once a year, whichever comes first
							9132937 Gasket-Oil Drain plug	
					6Cyl 4.7Qts	6Cyl 93178952	90409376 Drain Plug	
							11016282 Gasket-Oil Drain plug	

Model	Year	Engine	Recommended Oil Type	Recommended Viscosity	Oil Quantity	Oil Filter Part Number	Associated Parts	Service Interval
9-3	1999-2002 incl 2003 Convertible	B204, B205, B235	Full Synthetic 0W-40	API SJ, CCMC G4/ G5, SAE 5W-30, 0W-30, 5W-40, ILSAC GF-3 specification is approved for use in applicable markets. Oils with viscosity's 0W-40/0W-50 of well-known brands and fulfilling minimum ACEA A3/B3 are also recommended, especially for extreme driving conditions.	4.2Qts	93186554 4-Cyl	9132929 Drain Plug	Every 5000 miles or once a year, whichever comes first
							9132937 Gasket-Oil Drain plug	
9-5	1999-2009	B235, B308t	Full Synthetic 0W-40	API SM or higher, GM-LL-A-025, ACEA A3/B3, SAE 0W-30, 0W-40, 5W-30 or 0W-40	4Cyl 4.2Qts	93186554 ALL Engines	9132929 Drain Plug	Every 5000 miles or once a year, whichever comes first
					6Cyl 4.6Qts		9132937 Gasket-Oil Drain plug	
9-3 SS	2003-2011	B207, B284	Full Synthetic 0W-40	API SM or higher, GM-LL-A-025, ACEA A3/B3, SAE 0W-30, 0W-40, 5W-30 or 0W-40	4Cyl 6.3Qts	4Cyl 12605566	11562588 Drain Plug	Every 5000 miles or once a year, whichever comes first
							3536966 Gasket-Oil Drain plug	
							12580255 Oil Filter Housing O-ring	
					6Cyl 6.0Qts	6Cyl 93186310	9132929 Drain Plug	
							12616850 Gasket-Oil Drain plug	
							12577653 Oil Filter O-ring included with Filter 93186310	

Model	Year	Engine	Recommended Oil Type	Recommended Viscosity	Oil Quantity	Oil Filter Part Number	Associated Parts	Service Interval
9-2X	2005-2006	EJ205, EJ253, EJ255	Full Synthetic 5W-30	API SM, ILSAC GF-4 or higher SAE 5W-30 For areas with very high temperatures or used for heavy-duty applications SAE 30, 40, 10W-50, 20W-40, 20W-50 are recommended	4.2Qts	32009814	32008482 Drain Plug	Every 5000 miles or once a year, whichever comes first
							32005452 Gasket-Oil Drain plug	
9-7X	2005-2009	LL8 = 4.2L Inline 6 LH6 = 5.3L V8, LS2 = 6.0L V8	Full Synthetic 5W-30	LL8/LH6 - GM6094M SAE 5W-30 API SM. Below 20°F use SAE 5W-30 or SAE 0W-30 synthetic oil. LS2 - 6.0 Liter V8 GM4718M Mobil 1 Synthetic 5W-30	LL8 6Cyl 7Qts	LL8 6Cyl 19210285	11562588 Drain Plug	Every 5000 miles or once a year, whichever comes first
					LH6/LS2 V8 6Qts	LH6/LS2 V8 19303975	Oil Gasket only comes with drain plug	
							11562588 Drain Plug	
							Oil Gasket only comes with drain plug	
NG 9-5	2010-2011	A20NHT 4 Cyl, A28NER V6	Full Synthetic 5W-30 Annual Protection	dexos1™ Gen 2 GM4718M ACEA A3/B4 API SN SAE 5W-30, 5W-40, 0W-30 or 0W-40	4Cyl 6.3Qts	4Cyl 12605566	11562588 Drain Plug	Every 5000 miles or once a year, whichever comes first
					6Cyl 6.6Qts	6 Cyl 93186310	3536966 Gasket-Oil Drain plug	
							11562588 Drain Plug	
							12577653 Oil Filter O-ring included with Filter 93186310	
							12616850 Gasket-Oil Drain plug	

Model	Year	Engine	Recommended Oil Type	Recommended Viscosity	Oil Quantity	Oil Filter Part Number	Associated Parts	Service Interval
9-4X	2011	A28NER 2.8V6-T, A30YH 3.0V6i	Full Synthetic 5W-30 Annual Protection	dexos1™ Gen 2 GM4718M ACEA A3/B4 API SN SAE 5W-30 , 5W-40, 0W-30 or 0W-40	A28NER 2.8L 6Qts	A28NER 93186310	11562588 Drain Plug	Every 5000 miles or once a year, whichever comes first
							12577653 Oil Filter O-ring included with Filter 93186310	
							12616850 Gasket-Oil Drain plug	
					A30YH 3.0L 6Qts	A30YH 89017525	11562588 Drain Plug	
						12616850 Gasket-oil plug		

About Orio

Orio North America is a wholly owned subsidiary of Orio AB, the exclusive provider of Saab Original parts and service globally, headquartered in Nyköping, Sweden.

Headquartered in Bethlehem, Pennsylvania, Orio North America operates a 120,000-square-foot parts distribution center. Orio AB operates an approximately 1-million-square-foot distribution center south of Stockholm, Sweden.

North America is the largest market for Saab, with approximately 400,000 units in operation. Today, Orio North America has approximately 200 dedicated Saab official service centers, a B2B e-commerce portal with 250 Independent Repair Shop customers and a B2C website for Saab.



[orio.com](#) | [repair.orioautoparts.com](#) | [thesaabsite.com](#)
 Phone: 888-711-6862 | Email: saabparts@orio.com
Orio AB | 2550 Brodhead Road, Bethlehem, PA 18020 United States